


照光式／ILLUMINATED SWITCHES

スナップインタイプ／Snap-in type

DS-413
(with LED)




パネル板厚 Panel Thickness	1~3.0mm
取付穴参考寸法 Mounting Hole	30.2±0.1×11±0.1mm

ツマミカラー Knob Color		
白 (LED赤) White (LED Red)	○	
黒 (LED赤) Black (LED Red)	△	

注記 (NOTE)
○=標準色 Standard Color
△=受注生産 Only for large quantity order

端子形状 Shape of Terminal	タブ端子(LED) #110 Tab Terminal (LED) #110	タブ端子(LED) #110 Tab Terminal (LED) #110
		タブ端子 #250 Tab Terminal #250



LED仕様 Specifications

絶対最大定格 (周囲温度 $T_a=25^\circ\text{C}$)
Absolute maximum ratings

$T_a=25^\circ\text{C}$

Color	Pd (mW)	IF (mA)	VR (V)	Topr (°C)	Tstg (°C)
Red	75	30	4	-30~+85	-30~+100

動作特性 (順電流 $I_F=10\text{mA}$, 周囲温度 $T_a=25^\circ\text{C}$, 逆電圧 $V_r=4\text{V}$)
Electro-optical characteristics $I_F=10\text{mA}$, $T_a=25^\circ\text{C}$, $V_r=4\text{V}$

Color	VF (Typ.) (V)	IR(Max) (μA)	IV(mcd)		λP (Typ.) (nm)	$\Delta\lambda$ (Typ.) (nm)
			Min.	Typ.		
Red	2.1	100	0.4	0.8	700	100

品番 PARTS NO.	回路 CIRCUIT	スイッチ特性 SWITCHING FUNCTION	電流容量 RATING	絶縁抵抗 INSULATION RESISTANCE	絶縁耐圧 VOLTAGE BREAKDOWN	接触抵抗 CONTACT RESISTANCE
DS-413	SPST (2P)	ON-OFF	10A. 125V. AC	DC. 500V 100M Ω 以上 (MIN)	AC. 1000V 1分間 (Minute)	20m Ω 以下 (MAX)